

Technical Specifications

Model w1112kr	PL465AA
Processor & Speed	AMD Athlon (B) XP3200+ 2.20GHz/400
Chipset	VIA KM400A
Motherboard	Kelut-GL6E (A7V8X-LA)
RAM	512/3200 MB 400DDR SDRAM (runs@333MHz)
Maximum	2 GB (2x1024MB DDR SDRAM)
Sockets	Two 184-pin DDR DIMMs
Size	128, 256, 512 AND 1024 MB DDR DIMMs
Free DIMM Sockets	One
Pairs Required	No
Type Supported	JEDEC unbuffered DDR SDRAM DIMM specification
Cache	128 KB L1, 512 KB L2 Integrated on Processor module
Hard Drive	160 GB (7200 rpm)
Optical Drive	CD-RW/DVD-ROM Drive 48x32x16x48 48X- Write /32X - Re-write /16x- DVD Read 48X - CD-ROM Read
Average Random Access	DVD =115ms / CD-ROM =95ms
Transfer Rate	DVD = 21.6/sec. / CD-ROM = 7.2MB/sec.
Diskette Drive	None
9 in 1 Card Reader	Compact Flash I/II, Memory Stick/PRO, MMC/SD, Smart Media, xD, Microdrive
Video Graphics	AGP 8X Graphics Card
Controller	nVidia FX5200XT
Video Memory	128 MB DDR, not upgradeable
Video Connectors	Composite & S-Video - NTSC
Network Card	10/100 BaseT, Integrated
1394 Card	IEEE-1394, Integrated
Sound	AC'97, 6 Channel, Integrated on MB
Controller	Realtek ALC658
Chassis	Palisades, 250HV PSU
USB Interface Specification	USB 2.0
External I/O Rear Connectors	4= USB, 1=1394, Serial, Parallel, Line-In, Line-Out; Microphone
External I/O Front Connectors	2= USB, 1=1394, Microphone, Headphone
Expansion Slots (Total)	3= PCI, 1=AGP
Expansion Slots (FREE)	3= PCI
Drive Bays (Total)	Two 5.25" external, One 3.5" internal
Drive Bays (FREE)	One 5.25" external
Keyboard/Mouse	One-touch Enhanced Keyboard, PS/2 Optical scrolling mouse

Copyright Hewlett-Packard Co. 1994-2004
This information is subject to change without notice and
is provided "as is" with no warranty.
Hewlett-Packard shall not be liable for any direct,
indirect, special, incidental or consequential damages
in connection with the use of this material.